3-INCH METER INSTALLATION

- (1.) 2 2" METERS PROVIDED AND INSTALLED BY CITY OF TUMWATER
- (2) 3" METER MANIFOLD (WITH TWO 2" METER SETS)
- (3) 2 3" MJ X MJ GATE VALVES (RESTRAINED BOTH SIDES)
- (4.) 2 3" FLANGE COUPLING ADAPTERS
- (5.) 4 ANGLE BALL STOPS
- 6.) 2 3" X 36" LENGTH I.P. PLAIN ENDS
- (7.) 3" PLAIN END I.P.
- (8.) 2 6" SLEEVES
- (9.) 2 MEGALUG MID-SPAN RESTRAINTS

4-INCH METER INSTALLATION

- (1.) 3 2" METERS PROVIDED AND INSTALLED BY CITY OF TUMWATER
- (2) 4" METER MANIFOLD (WITH THREE 2" METER SETS)
- (3.) 2 4" MJ X MJ GATE VALVES (RESTRAINED BOTH SIDES)
- (4.) 2 4" FLANGE COUPLING ADAPTERS
- (5.) 6 ANGLE BALL STOPS
- (6.) 2 4" X 36" LENGTH I.P. PLAIN ENDS
- (7.) 4" PLAIN END I.P.
- (8.) 2 8" SLEEVES
- (9.) 2 MEGALUG MID-SPAN RESTRAINTS

GENERAL NOTES:

- DRAINAGE MUST BE PROVIDED FOR THE METER VAULT.
- METER VAULT MAY BE EXTENDED IN LENGTH WHEN P.R.V. IS REQUIRED.
- ON ALL METERS 3" INCHES AND ABOVE, A FLEX-COUPLING SHALL BE INSTALLED IN THE OUTLET LINE WITHIN THE METER BOX.
- VAULTS SHALL BE EQUIPPED WITH LADDERS WHEN OVER 4' IN DEPTH.
- GROUT ANNULAR SPACE BETWEEN VAULT WALL AND PIPE.

ALL SIX-INCH AND EIGHT-INCH WATER SERVICE CONNECTIONS MUST BE PRE-APPROVED BY THE PUBLIC WORKS DEPARTMENT, 754-4150.

CITY OF TUMWATER, WASHINGTON DEPT. OF PUBLIC WORKS MATERIALS LIST FOR 3" & 4" MANIFOLD WATER METERS APPROVED BY: DWG. NO. WA-32 CITY ENGINEER CK'D BY **NOT TO** DWG. BY DATE DES. **SCALE** PW PW KMC JULY 2014