



GENERAL NOTES:

1. PAD AND PEDESTAL MOUNTS SHALL BE COMERCIAL CONCRETE UNLESS NOTED OTHERWISE ON PLANS.
2. WHERE PAD OF PEDESTAL MOUNTS ARE LOCATED IN A SIDEWALK, CONSTRUCT MOUNT TOP FLUSH WITH SIDEWALK GRADE, OMITTING CHAMFER WHERE TOP AND SIDEWALK ABUT.
3. PAD MOUNT DESIGN IS TYPICAL: CONTRACTOR SHALL UTILIZE CABINET ON BASE WITH RESPECT TO CONDUIT PLACEMENT. CONTRACTOR SHALL SUBMIT FOR APPROVAL A PROPOSED DESIGN WITH PLAN, ELEVATION AND ANY RELEVANT SECTION VIEW.
4. CABINET SHALL BE ATTACHED WITH AASHTO M 164 CHEMICALLY BONDED ANCHOR TO EXISTING PAD MOUNTS. ANCHOR INSTALLATIONS SHALL BE PER MANUFACTURER'S RECOMMENDATIONS IN DRY CONDITIONS.
5. PLACE A SILICONE SEAL BETWEEN THE CABINET FOUNDATION AND THE CABINET FOR THE PAD MOUNT DESIGN.
6. CABINET AND SERVICE TO BE CENTERED ON BASE.

CITY OF TUMWATER, WASHINGTON DEPT. OF PUBLIC WORKS				
SIGNAL CABINET FOUNDATION				
APPROVED BY:				DWG. NO.
CITY ENGINEER				ST-18
DES. PW	DWG. BY PW	CK'D BY MW	DATE JAN. 2015	NOT TO SCALE