



GENERAL NOTE:

1. POST MATERIAL IS TO BE SQUARE TELESPIRE PIPE.
2. SIGN IS TO BE ON CENTER AND 3" FROM TOP OF BARRIER.
3. IN ORDER TO PRESERVE WEATHER PROOFING DO NOT RE-CUT LUMBER ENDS.
4. MARKINGS FOR BARRICADE SHALL BE ALTERNATE RED AND WHITE STRIPES (SLOPING DOWNWARD, PER MUTCD, AT AN ANGLE OF 45° TO CURB).
5. THE ENTIRE AREA OF RED AND WHITE STRIPES SHALL BE REFLECTORIZED SO AS TO BE VISIBLE UNDER NORMAL ATMOSPHERIC CONDITIONS FROM A MINIMUM OF 1,000 FEET WHEN ILLUMINATED BY THE LOW BEAMS OF STANDARD AUTOMOBILE HEADLIGHTS.
6. BARRICADE SECTION SHALL EXTEND TO THE LIMITS OF THE PAVED SURFACE.

CITY OF TUMWATER, WASHINGTON DEPT. OF PUBLIC WORKS			
PERMANENT BARRICADE			
APPROVED			DWG. NO.
_____ CITY ENGINEER			4-5.9
DES PW	DWN JC	CKD MW	DATE 2/8/18